


## Thermoelectric cooling unit



### Description


<b>Order Number:</b>	3030305
<b>Brand Name:</b>	SoliTherm Peltier
<b>Housing Material:</b>	Stainless steel AISI 304 (V2A)
<b>Ingress Protection:</b>	IP 66 / UL Type 12, 4, 4X
<b>Note:</b>	The torque for the mounting nuts should be 4.5 Nm.
<b>Approvals:</b>	CE, cURus
<b>Accessories:</b>	 <a href="#">Condensate Kit 3030 / 3050</a>

## Technical Data

<b>Cooling capacity L35L35:</b>	30 W
<b>Operating Temperature Range:</b>	-20°C - 70°C
<b>UL temperature range:</b>	-20°C - 65°C
<b>Air flow volume (system / unimpeded):</b>	Ambient air circuit: 39 / 75 m <sup>3</sup> /h Cabinet air circuit: 20 / 62 m <sup>3</sup> /h
<b>Mounting:</b>	Wall mounted (with frame)
<b>Dimensions A x B x C (D+E):</b>	212 x 158 x 132 mm
<b>Weight:</b>	2.6 kg
<b>Cut out dimensions:</b>	180 x 128 mm
<b>Voltage / Frequency:</b>	12 V DC
<b>Current L35L35:</b>	2.8 A
<b>Starting current:</b>	4.3 A
<b>Max. current:</b>	2.9 A
<b>Nominal power L35L35:</b>	34 W
<b>Max. power:</b>	35 W
<b>Fuse:</b>	5 A (T)
<b>Connection:</b>	Connection terminal block


Please click on the graphics to download.  
 More CAD drawings can be found under [Product Download](#).  
 > [Overview Product Group Cooling Units - PELTIER](#)

**Performance graph:**



click image to enlarge

**Cut Out Dimension:**



click image to enlarge

## Order Information

<b>Stainless steel AISI 316 (V4A) housing part no.</b>	30303054
<b>Box dimension</b>	244 x 187 x 174 mm
<b>Gross weight</b>	2.8 kg
<b>Taric code</b>	84158300
<b>GTIN (EAN)</b>	5350604350021