

Control Cabinet Air Conditioner



Description

Order Number:	43300001
Brand Name:	COMPACT INDOOR
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress Protection:	IP 54 / TYPE 12
Approvals:	CE, cURus, cULus


Technical Data

Cooling capacity L35L35:	3 kW @ 50 Hz 3 kW @ 60 Hz
Cooling capacity L35L50:	2.38 kW @ 50 Hz 2.51 kW @ 60 Hz
Compressor type:	Rotary piston compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	900 g / 31.7 oz
High / low Pressure:	29.5 / 6 bar 425 / 88 psig
Operating Temperature Range:	10°C - 55°C
Air flow volume (system / unimpeded):	Ambient air circuit: 750 / 1200 m ³ /h Cabinet air circuit: 860 / 1200 m ³ /h
Mounting:	Wall mounted
Dimensions A x B x C (D+E):	1,230 x 500 x 340 mm
Weight:	67.5 kg
Cut out dimensions:	1,130 x 430 mm
Voltage / Frequency:	230 V ~ 50/60 Hz
UL Voltage / Frequency:	230 V ~ 60 Hz
Current L35L35:	5.6 A @ 50 Hz 7.6 A @ 60 Hz
Starting current:	25.1 A
Max. current:	9.2 A
Nominal power L35L35:	1,33 kW @ 50 Hz 1,69 kW @ 60 Hz
Max. power:	1,61 kW @ 50 Hz 2,06 kW @ 60 Hz
Fuse:	16 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block

Please click on the graphics to download.
 More CAD drawings can be found under [Product Download](#).


> [Overview Product Group Cooling Units - COMPACT](#)

Performance graph:




[click image to enlarge](#)

Air flow:



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)

Order Information

Stainless steel housing part no.	4330002
With condensate evaporation part no.	43300101
Box dimensions	1,265 x 543 x 375 mm
Gross weight	71.5 kg
Taric code	84158200
GTIN (EAN)	5350604361041