

Cooling unit NEMA / type 4X



Description

Order Number:	57200182
Brand Name:	Compact Outdoor
Housing Material:	Stainless steel AISI 304 (V2A)
IP protection class to EN 60 529:	IP 56 / Type 12, 3, 3R, 4, 4X
Included:	With enclosure heater and aluminium filter
Approvals:	CE, cURus, cULus
UL File Number:	cURus (SA32278), cULus (E498756)

Technical Data


Cooling capacity L35L35 (EN14511-3):	2000 W @ 50 Hz 2000 W @ 60 Hz
Cooling capacity L35L50 (EN14511-3):	1600 W @ 50 Hz 1600 W @ 60 Hz
Enclosure heater:	1000 W
Compressor type:	Rotary piston compressor
Refrigerant / GWP:	R513A / 630
Refrigerant charge:	522 g / 18.4 oz
High / low Pressure:	29 / 6 bar 425 / 88 psig
Air flow volume (system / unimpeded):	Ambient air circuit: 655 / 1200 m³/h Cabinet air circuit: 400 / 850 m³/h
Operating Temperature Range:	-40°C - 55°C
Mounting:	Wall mounted
Dimensions A x B x C (D+E):	1,150 x 395 x 270 mm
Weight:	49 kg
Voltage / Frequency:	230 V ~ 50/60 Hz
UL Voltage / Frequency:	230 V ~ 60 Hz
Current L35L35:	5.4 A @ 50 Hz 6.8 A @ 60 Hz
Starting current:	16 A
Max. current:	8.6 A
Nominal power L35L35:	1193 W @ 50 Hz 1491 W @ 60 Hz
Max. power:	1468 W @ 50 Hz 1810 W @ 60 Hz
Fuse:	13 A (T)
Short-circuit current rating:	5 kA
Connection:	4-pole terminal block for power 5-pole terminal block for signals 3-pole terminal block for RS 485

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).


> [Overview Product Group COMPACT OUTDOOR - cooling units NEMA / Type 4X](#)

Performance graph:



click image to enlarge

Cut Out Dimension:



click image to enlarge

Order Information

In stainless steel 316 (V4A) part no.	57200184
Box dimensions	1,190 x 443 x 310 mm
Gross weight	52 kg
Taric code	84158200