


Cabinet cooling unit



Description

Order Number:	850320001
Brand Name:	SLIMLINE PRO
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
IP protection class to EN 60 529:	IP 55 / Type 12
Approvals:	CE, cURus, cULus
Accessories:	 Gasket Kit Type 4  Cold Air Outlet Duct 8503/06  Washable Aluminium Filter 8503/06

Technical Data

Cooling capacity L35L35 (EN14511-3):	350 W @ 50 Hz 380 W @ 60 Hz
Cooling capacity L35L50 (EN14511-3):	200 W @ 50 Hz 215 W @ 60 Hz
EER L35L35:	1.13
Compressor type:	Rotary Piston
Refrigerant / GWP:	R 513A / 630
Refrigerant charge:	92 g / 3.2 oz
High / low Pressure:	28 / 6 bar 406 / 88 psi
Air flow volume (system / unimpeded):	Ambient air circuit: 225 / 408 m³/h Cabinet air circuit: 122 / 180 m³/h
Operating Temperature Range:	10°C - 55°C
UL temperature range:	10°C - 55°C
Mounting:	Wall mounted / recessed
Dimensions A x B x C (D+E):	600 x 250 x 187.6 (48.6+139) mm
Weight:	15.5 kg
Voltage / Frequency:	400/460 V - 50/60 Hz 2~
UL Voltage / Frequency:	460 V / 60Hz 2~
Current L35L35:	0.9 A @ 50 Hz 0.9 A @ 60 Hz
Starting current:	2.5 A
Max. current:	1.0 A
Nominal power L35L35:	310 W @ 50 Hz 310 W @ 60 Hz
Max. power:	380 W
Fuse:	15 A (T)
Max circuit ampacity:	15 A
Short-circuit current rating:	5 kA
Rated current compressor:	0.6 A


Full load current fans:	0.15 A
Connection:	4 pole terminal for power 5 pole terminal for signals 3 pole terminal for RS485

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).


> [Overview Product Group SLIMLINE PRO - cooling units in a new design](#)

Performance graph:



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)

Order Information

Box dimensions	692 x 285 x 242 mm
Gross weight	17 Kg
Taric Code	84158200
GTIN (EAN)	5350604390003